

HYDRAGUARD LIMITED

ANTIFOAM

ANTIFOAM is a potent water antifoam. This product excels at stopping foam. It is particularly good at controlling foaming created during cooling tower cleaning. The product is highly concentrated. Small amounts will prevent foaming in large systems. The product's performance is also unaffected by overdosing.

ADVANTAGES

Can prevent scale in the presence of hardness slippage due to softener malfunction.

- ◆ a good antifoam
- ◆ Highly concentrated
- ◆ Unaffected by overfeed
- ◆ low toxicity

HOW MUCH TO USE

Due to the wide variety of causes of foaming, exact dosages cannot be determined in advance. Typical dosages of 10—100 ppm are sufficient. A certain amount of trial and error may be necessary to find the optimum dosage.

METHOD OF APPLICATION

ANTIFOAM may be added to any part of the system where there is good mixing. The product can be pumped in or hand fed as necessary. Usually product is slug dosed.

PROPERTIES

Appearance:	Yellowish, thick liquid
Density:	0.9
pH of 1% solution:	6.8

HANDLING AND STORAGE

Standard chemical precautions should be taken when handling this product. Wear gloves and goggles. Use in well-ventilated spaces. Store in a cool place. Consult Health and Safety sheet for further information.

PACKAGING

ANTIFOAM is available in 20l containers.

PRODUCT DATA

Hydraguard Limited
Rose Croft
Newton on Rawcliffe
Pickering
North Yorkshire YO18 8QE

Tel No. 01751 475964